

Gallop Field Shelter Specification

Mobile Field Shelter

Ridge height	2.900m
Eaves height	2.350m
Threshold height	110mm
Opening size	1.880m (w) x 2.090m (h)- from ground to top of opening is 2.200m
Overhang	1050mm (3.6m models) 650mm (3.0m models) overhang lined with 9mm ply
Skid	150x75mm Pressure treated skid with galvanised towing points at either end
Framework	Constructed from 63x38 (75x50cls) Pressure treated timber at 600mm centres. Studwork doubles at door apertures. Additional 63x38 cls cross members to 1.22m height.
Cladding	Ex 16mm Pressure treated overlap shiplap.
Kick-boarding	Lined 1.22m with 11mm OSB
Roof trusses	Constructed from 113x38mm cls Tanalith E treated timber. All trusses fixed to sections with 100mm or 150mm timberlock screws.
Purlins	100x47mm Pressure treated timber. Purlins fixed to trusses with 100mm or 150mm timberlock screws.
Roofing	Genuine black onduline with black onduline ridge capping. Roof lining available (see price lists)
Guttering	Nil
Treatment	All timbers with exception of any sheet material are vacuum/pressure impregnated treated. Standard colour of finish light green fading to natural colour. Alternative colour finishes of dark brown and black available.

Mobile combination units

(as field shelter with the following differences for the tack room section)

Opening	Tack room door width 0.90m wide x 2.0m high
Interior lining	Unlined
Door	Supplied and fitted with three 16" hinges, 6" tower bolt and cabin hook to secure door when open. Ironmongery fittings include staple and hasp for extra protection.
Floor	No Floor
Roof lining	Face of truss between stable and tack room also boarded with 11mm OSB.