

## Mobile Field Shelter

Ridge height	2.900m
Eaves height	2.350m
Threshold height	110mm
Opening size	1.880m (w) x 2.090m (h)- from ground to top of opening is 2.200m
Overhang	1050mm (3.6m models) 650mm (3.0m models) overhang lined with 9mm ply
Skid	150 x 75mm Pressure treated skid with galvanised towing points at either end
framework	Constructed from 63 x 38 cls Tanalith E treated timber at 600mm centres. Studwork doubles at door apertures. Additional 63 x 38 cls cross members to 1.22m height.
Cladding	Ex 16mm Pressure treated overlap shiplap.
Kick-boarding	Lined 1.22m with 11mm OSB
Roof trusses	Constructed from 113x38mm cls Tanalith E treated timber. All trusses fixed to sections with 100mm or 150mm timberlock screws.
Purlins	C24 Graded 47x100mm Pressure treated timber. Purlins fixed to trusses with 100mm or 150mm timberlock screws.
Roofing	Genuine black onduline with black onduline ridge capping. Roof lining available (see price lists)
Guttering	Nil
Treatment	All timbers with exception of any sheet material are vacuum/pressure impregnated treated. Standard colour of finish light green fading to natural colour. Alternative colour finishes of dark brown and black available.

## \*\*\*NO TOW CHAINS PROVIDED\*\*\*

### Mobile combination units

(as field shelter with the following differences for the tack room section)

Opening	Tack room door width 0.90m wide x 2.0m high
Interior lining	Unlined
Door	Supplied and fitted with three 450mm hinges, 150mm tower bolt and cabin hook to secure door when open. Ironmongery fittings include staple and hasp for extra protection.
Floor	47x100mm Pressure treated joists at a maximum 600mm centres. Covered with 18mm flooring
Roof lining	Face of truss between stable and tack room also boarded with 11mm OSB.